



CORFU

Technical specifications | Technische Daten | Spécifications techniques

Manufacturing technique Herstellungstechnik Technique de fabrication		1/10 Cut Pile 1/10 1/10
Pile composition Material der Nutzschrift Composition du velours		100% PA 6.0 Crealon 
Secondary backing Rückenausstattung Dossier		Superback
Width Breite Largeur		400 cm
Roll length Rollenlänge Longeur du rouleau		25 m
Pile height Polhöhe Hauteur du velours	ISO 1766	3,8 mm
Pile weight Polgewicht Poids du velours		360 g/m ²
Total height Gesamthöhe Hauteur totale	ISO 1765	9,4 mm
Total weight Gesamtgewicht Poids total	ISO 8543	1720 g/m ²

Number of tufts Noppenzahl Nombre de points	ISO 1763	202.800 /m ²
Fastness to rubbing (dry) Reibechtheit (trocken) Solidité au frottement (sec)	ISO 105 X12	4-5
Fastness to rubbing (wet) Reibechtheit (nass) Solidité au frottement (humide)	ISO 105 X12	4-5
Water fastness Wasserechtheit Solidité à l'eau	ISO 105 E01	4-5
Fastness to light Lichtechtheit Solidité à la lumière	ISO 105 B2	5
Thermal resistance Wärmedurchlasswiderstand Résistance thermique	ISO 8302	0,16 m ² K/W
Impact sound insulation Trittschalldämmung Réduction de la transmission du bruit de choc	ISO 140 - 8	27 dB
DOP Nr / DOP n°		1087#01102/.../SI



CARUS®

BIG Floorcoverings nv
Rijksweg 442
B-8710 Wielsbeke - Belgium

Showroom
Boffonstraat 3
B-8710 Wielsbeke - Belgium

www.carusflooring.com
carus@bintg.com
T +32 (0)56 67 42 11 - F +32 (0)56 67 48 30