

Tempo




PRODUCT INFORMATION		
Level of use	EN ISO 10874	23 - 33
Total thickness	EN ISO 24346	2,0 mm
Wear layer	EN ISO 24340	0,50 mm
Wear layer PUR treatment		Superguard®
Total weight g/m ²	EN ISO 23997	2.393

SIZE & PACKING		
Width	2 m	4 m
Length	25 m	25 m
Weight	124 kg	248 kg

TEST RESULTS		
Inflammability	EN 13501	Bfl-S1
Scratch resistance	EN 13893	DS
Slip restraint	DIN 51130	R10
Residual indentation	EN ISO 24343-1	Norm: ≤ 0,20 mm - Average result measured 0,09mm
Furniture leg resistance	EN ISO 16581	No cracks, no damage
Curling	EN ISO 23999	≤ 8 mm
Electrical resistance	EN 1081	≤ 10 ⁹ Ohm
Dimensional stability	EN ISO 23999	Norm: ≤ 0,40 % - Average result measured
Heat insulation	EN 12524	0,25 w/(m.K)
Thermal resistance R	EN ISO 12664	0,0080 m ² .K/W
Electrostatic performance	EN 1815	< 2 kV
Acoustic insulation	EN ISO 717-2	8 dB
Castor chair resistance	EN ISO 4918	No damage to wearlayer, no delamination
Stain resistance	EN ISO 26987	Very good
Light fastness	EN ISO 105-B02	≥6
Underfloor heating	EN 12524	Suitable
Warranty (year)		12 Residential 5 Commercial

The warranty covers manufacturing defects and premature wear in the event of normal use.

The samples in this presentation are only cuttings of the respective products and show only a small part of the overall design and colour. With regard to colour printing of the photographic images, it is only possible to give a provisional representation of the colour.



CE TBC